




N = WPMA80 | PMA100


High pressure multistage horizontal pumps with

AXIAL SUCTION



PMA80 PMA100

Sizes from-to	DNm 80 DNm 100
Flow Rate up to	55 l/s
Head up to	1000 m
Suction port	PN25 (PMA-PMAS) PN40 (PMAH)
Delivery port	PN40 (PMA) PN63 (PMAS) PN100 (PMAH)
Rotation speed (rpm)	1.450 - 3.500



IDEAL FOR

SNOWMAKING

WATER SUPPLY

INDUSTRIAL APPLICATIONS

FIRE-FIGHTING

IRRIGATION



WHY CHOOSE PMA?

PRESSURE UP TO 100 BAR

- Impellers with axial thrust compensation system
- High thicknesses of the casting components and high performance materials

2 **HIGH ENERGY SAVING**

- High-efficiency hydraulics: best in class efficiency
- Performance guaranteed over time: replaceable wear rings

3 REDUCED INSTALLATION COSTS

- Simple installation: suction casing axial to the pipeline
- Easy pump-motor alignment: innovative baseframes

4 **LOW NPSH VALUES**


- · Reduces the risk of cavitation
- Reliable operation even in lifting installations

EASY MAINTENANCE

- Reduced maintenance: grease lubricated bearing on the delivery side
- Quick replacement of the sleeve and bushing from the suction side

PMA65

PMA125





For information

Tel. +39 059 897611 | Fax +39 059 897897 | info@caprari.it





You can also

follow us on

