

## Series description: Rmot Stratos/-D

Wilo-Stratos/-D RMOT



Similar to figure

---

### Equipment/function

**For Wilo Stratos/Stratos-D pumps in the event of replacement**

- Functional unit with motor, impeller and electronic module

---

### Series

Rmot Stratos/-D



## Product list: Rmot Stratos/-D

Product description	Article number
Spare motor Stratos 25/1-6 RMOT.	2095080
Spare motor Stratos 25/1-8 RMOT.	2095081
Spare motor Stratos 30/1-6 RMOT.	2095082
Spare motor Stratos 30 (-D 32)/1-8 RMOT.	2095083
Spare motor Stratos 30/1-12 RMOT.	2095084
Spare motor Stratos /-D 32/1-12 RMOT.	2095085
Spare motor Stratos 40/1-4 RMOT.	2095086
Spare motor Stratos /-D 40/1-8 RMOT.	2095087
Spare motor Stratos /-D 40/1-12 RMOT.	2095088
Spare motor Stratos /-D 50/1-8 RMOT.	2095089
Spare motor Stratos /-D 50/1-9 RMOT.	2095090
Spare motor Stratos /-D 50/1-12 RMOT.	2095091
Spare motor Stratos 65/1-9 RMOT.	2095092
Spare motor Stratos /-D 65/1-12 RMOT.	2095093
Spare motor Stratos /-D 80/1-12 RMOT.	2095094
Spare motor Stratos 100/1-12 RMOT.	2095095
Spare motor Stratos 25/1-4 RMOT.	2119570
Spare motor Stratos 25/1-10 RMOT.	2119571
Spare motor Stratos 30/1-4 RMOT.	2119572
Spare motor Stratos 30/1-10 RMOT.	2119573
Spare motor Stratos 32/1-10 RMOT.	2119574
Spare motor Stratos 40/1-10 RMOT.	2119575
Spare motor Stratos 50/1-10 RMOT.	2119576
Spare motor Stratos /-D 40/1-16 RMOT.	2146337
Spare motor Stratos /-D 50/1-16 RMOT.	2146338
Spare motor Stratos /-D 65/1-16 RMOT.	2146339
Spare motor Stratos 25/1-12 RMOT.	2146520
Spare motor Stratos 50/1-6 RMOT	2151883
Spare motor Stratos 65/1-6 RMOT	2151884
Spare motor Stratos 100/1-6 RMOT	2151886
Spare motor Stratos/-D 65/1-12 RMOT. (SW≥6.12)	2163268
Spare motor Stratos/-D 80/1-6 RMOT.	2163269

## Data sheet: Spare motor Stratos 25/1-6 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	65,0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	3400 rpm
Motor size	23

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	2.50 kg
Weight gross (with packaging)	4.3 kg
Make	Wilo
Item no.	2095080

## Data sheet: Spare motor Stratos 25/1-8 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	100.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	3700 rpm
Motor size	23

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	2.50 kg
Weight gross (with packaging)	4.3 kg
Make	Wilo
Item no.	2095081

## Data sheet: Spare motor Stratos 30/1-6 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	65,0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	3400 rpm
Motor size	23

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	2.50 kg
Weight gross (with packaging)	4.3 kg
Make	Wilo
Item no.	2095082

## Data sheet: Spare motor Stratos 30 (-D 32)/1-8 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	100.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	3700 rpm
Motor size	23

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	2.50 kg
Weight gross (with packaging)	4.3 kg
Make	Wilo
Item no.	2095083

## Data sheet: Spare motor Stratos 30/1-12 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	200.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	4800 rpm
Motor size	33

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	3.30 kg
Weight gross (with packaging)	5.1 kg
Make	Wilo
Item no.	2095084

## Data sheet: Spare motor Stratos /-D 32/1-12 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	200.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	4800 rpm
Motor size	33

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	2.10 kg
Weight gross (with packaging)	3.5 kg
Make	Wilo
Item no.	2095085



## Data sheet: Spare motor Stratos 40/1-4 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	100.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	3700 rpm
Motor size	23

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	2.50 kg
Weight gross (with packaging)	4.3 kg
Make	Wilo
Item no.	2095086

## Data sheet: Spare motor Stratos /-D 40/1-8 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	200.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	4800 rpm
Motor size	33

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	3.80 kg
Weight gross (with packaging)	5.2 kg
Make	Wilo
Item no.	2095087

## Data sheet: Spare motor Stratos /-D 40/1-12 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	450.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	4600 rpm
Motor size	43

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	5.80 kg
Weight gross (with packaging)	7.2 kg
Make	Wilo
Item no.	2095088

## Data sheet: Spare motor Stratos /-D 50/1-8 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	200.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	4800 rpm
Motor size	33

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	3.40 kg
Weight gross (with packaging)	5.2 kg
Make	Wilo
Item no.	2095089

## Data sheet: Spare motor Stratos /-D 50/1-9 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	400.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	4100 rpm
Motor size	43

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	5.80 kg
Weight gross (with packaging)	7.2 kg
Make	Wilo
Item no.	2095090

## Data sheet: Spare motor Stratos /-D 50/1-12 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	500.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	4600 rpm
Motor size	43

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	5.80 kg
Weight gross (with packaging)	7.2 kg
Make	Wilo
Item no.	2095091

## Data sheet: Spare motor Stratos 65/1-9 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	500.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	4600 rpm
Motor size	43

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	5.80 kg
Weight gross (with packaging)	7.2 kg
Make	Wilo
Item no.	2095092

## Data sheet: Spare motor Stratos /-D 65/1-12 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	650.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	950 rpm
Max. speed	3300 rpm
Motor size	53

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	470 mm
Length with packaging	470 mm
Width <i>W</i>	430 mm
Width with packaging	430 mm
Height <i>H</i>	300 mm
Height with packaging	300 mm
Net weight, approx. <i>m</i>	9.60 kg
Weight gross (with packaging)	11.6 kg
Make	Wilo
Item no.	2095093



## Data sheet: Spare motor Stratos /-D 80/1-12 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	1300,0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	900 rpm
Max. speed	3300 rpm
Motor size	63

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	470 mm
Length with packaging	470 mm
Width <i>W</i>	430 mm
Width with packaging	430 mm
Height <i>H</i>	300 mm
Height with packaging	300 mm
Net weight, approx. <i>m</i>	11,00 kg
Weight gross (with packaging)	13 kg
Make	Wilo
Item no.	2095094

## Data sheet: Spare motor Stratos 100/1-12 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	1300.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	900 rpm
Max. speed	3300 rpm
Motor size	63

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	470 mm
Length with packaging	470 mm
Width <i>W</i>	430 mm
Width with packaging	430 mm
Height <i>H</i>	300 mm
Height with packaging	300 mm
Net weight, approx. <i>m</i>	11.00 kg
Weight gross (with packaging)	13 kg
Make	Wilo
Item no.	2095095

## Data sheet: Spare motor Stratos 25/1-4 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	30,0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	2800 rpm
Motor size	23

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	2.50 kg
Weight gross (with packaging)	4.3 kg
Make	Wilo
Item no.	2119570

## Data sheet: Spare motor Stratos 25/1-10 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	140.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	4450 rpm
Motor size	23

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	2.50 kg
Weight gross (with packaging)	4.3 kg
Make	Wilo
Item no.	2119571

## Data sheet: Spare motor Stratos 30/1-4 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	30,0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	2800 rpm
Motor size	23

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	2.50 kg
Weight gross (with packaging)	4.3 kg
Make	Wilo
Item no.	2119572

## Data sheet: Spare motor Stratos 30/1-10 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	140.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	4450 rpm
Motor size	23

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	2.50 kg
Weight gross (with packaging)	4.3 kg
Make	Wilo
Item no.	2119573

## Data sheet: Spare motor Stratos 32/1-10 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	140.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	4450 rpm
Motor size	23

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	2.50 kg
Weight gross (with packaging)	4.3 kg
Make	Wilo
Item no.	2119574

## Data sheet: Spare motor Stratos 40/1-10 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	140.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	4450 rpm
Motor size	23

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	2.50 kg
Weight gross (with packaging)	4.3 kg
Make	Wilo
Item no.	2119575



## Data sheet: Spare motor Stratos 50/1-10 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	140.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	4450 rpm
Motor size	23

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	2.50 kg
Weight gross (with packaging)	4.3 kg
Make	Wilo
Item no.	2119576

## Data sheet: Spare motor Stratos /-D 40/1-16 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	650.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	950 rpm
Max. speed	3500 rpm
Motor size	53

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	470 mm
Length with packaging	470 mm
Width <i>W</i>	430 mm
Width with packaging	430 mm
Height <i>H</i>	300 mm
Height with packaging	300 mm
Net weight, approx. <i>m</i>	11.20 kg
Weight gross (with packaging)	14.1 kg
Make	Wilo
Item no.	2146337

## Data sheet: Spare motor Stratos /-D 50/1-16 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	1050,0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	950 rpm
Max. speed	3400 rpm
Motor size	63

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	470 mm
Length with packaging	470 mm
Width <i>W</i>	430 mm
Width with packaging	430 mm
Height <i>H</i>	300 mm
Height with packaging	300 mm
Net weight, approx. <i>m</i>	12,90 kg
Weight gross (with packaging)	15,2 kg
Make	Wilo
Item no.	2146338

## Data sheet: Spare motor Stratos /-D 65/1-16 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	1200,0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	950 rpm
Max. speed	3400 rpm
Motor size	63

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	470 mm
Length with packaging	470 mm
Width <i>W</i>	430 mm
Width with packaging	430 mm
Height <i>H</i>	300 mm
Height with packaging	300 mm
Net weight, approx. <i>m</i>	12,90 kg
Weight gross (with packaging)	15,2 kg
Make	Wilo
Item no.	2146339

## Data sheet: Spare motor Stratos 25/1-12 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	200.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	4800 rpm
Motor size	33

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	3.40 kg
Weight gross (with packaging)	5 kg
Make	Wilo
Item no.	2146520

## Data sheet: Spare motor Stratos 50/1-6 RMOT

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	200.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	4800 rpm
Motor size	33

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	3.40 kg
Weight gross (with packaging)	5.2 kg
Make	Wilo
Item no.	2151883

## Data sheet: Spare motor Stratos 65/1-6 RMOT

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	400.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	1400 rpm
Max. speed	3500 rpm
Motor size	43

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	340 mm
Length with packaging	340 mm
Width <i>W</i>	320 mm
Width with packaging	320 mm
Height <i>H</i>	260 mm
Height with packaging	260 mm
Net weight, approx. <i>m</i>	5.80 kg
Weight gross (with packaging)	7.2 kg
Make	Wilo
Item no.	2151884

## Data sheet: Spare motor Stratos 100/1-6 RMOT

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	850.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	900 rpm
Max. speed	2400 rpm
Motor size	63

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	470 mm
Length with packaging	470 mm
Width <i>W</i>	430 mm
Width with packaging	430 mm
Height <i>H</i>	300 mm
Height with packaging	300 mm
Net weight, approx. <i>m</i>	11.00 kg
Weight gross (with packaging)	13 kg
Make	Wilo
Item no.	2151886



## Data sheet: Spare motor Stratos/-D 65/1-12 RMOT. (SW $\geq$ 6.12)

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	650.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	950 rpm
Max. speed	2800 rpm
Motor size	53

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	470 mm
Length with packaging	470 mm
Width <i>W</i>	430 mm
Width with packaging	430 mm
Height <i>H</i>	300 mm
Height with packaging	300 mm
Net weight, approx. <i>m</i>	9.60 kg
Weight gross (with packaging)	11.6 kg
Make	Wilo
Item no.	2163268

## Data sheet: Spare motor Stratos/-D 80/1-6 RMOT.

### Technical data

Mains connection	1~230 V, 50/60 Hz
Threaded cable connection	1 x PG7
Rated power	850.0 W
IP protection class	IPX4D
Insulation class	F
Min. speed	900 rpm
Max. speed	2400 rpm
Motor size	63

### Operating data

Min. ambient temperature	-10 °C
Max. ambient temperature	40 °C

### Information for order placements

Length <i>L</i>	470 mm
Length with packaging	470 mm
Width <i>W</i>	430 mm
Width with packaging	430 mm
Height <i>H</i>	300 mm
Height with packaging	300 mm
Net weight, approx. <i>m</i>	11.00 kg
Weight gross (with packaging)	13 kg
Make	Wilo
Item no.	2163269